


SEALED ER COLLETS



Coolant flows exclusively through central hole, collet cuts are sealed with neoprene inserts (above Ø 3).
Working pressure: up to 40 Bar / 600 PSI



DIN 6499/A

COD.	DESCRIPTION	RANGE	d	L	STEP
5573 RF	ER 11 RF	1 ÷ 7	11,5	18	0,5
0364 RF	ER 16 RF	1 ÷ 10	17	27,5	0,5
0787 RF	ER 20 RF	2 ÷ 13	21	31,5	0,5
0996 RF	ER 25 RF	2 ÷ 16	26	34	0,5
0988 RF	ER 32 RF	3 ÷ 20	33	40	0,5
0821 RF	ER 40 RF	4 ÷ 26	41	46	1
4055 RF	ER 50 RF	6 ÷ 34	52	60	1

REDUCED SET OF COLLETS RF TYPE

COMPLETE SET OF COLLETS RF TYPE

	COD.	DESCRIPTION	DIAMETERS	N°OF COLLETS
IN PLASTIC TRAY	7587	ER 16 RF Reduced	Ø 4 - 6 - 8 -10	4
	7588	ER 20 RF Reduced	Ø 4 - 6 - 8 -10 -12	5
	7589	ER 25 RF Reduced	Ø 4 - 6 - 8 -10 -12 -16	6
	7590	ER 32 RF Reduced	Ø 4 - 6 - 8 -10 -12 -16 - 20	7
	7591	ER 40 RF Reduced	Ø 4 - 6 - 8 -10 -12 -16 - 20 - 25	8
IN WOODEN CASE	7600	ER 16 RF Reduced	Ø 4 - 6 - 8 -10	4
	7601	ER 20 RF Reduced	Ø 4 - 6 - 8 -10 -12	5
	7602	ER 25 RF Reduced	Ø 4 - 6 - 8 -10 -12 -16	6
	7603	ER 32 RF Reduced	Ø 4 - 6 - 8 -10 -12 -16 - 20	7
	7604	ER 40 RF Reduced	Ø 4 - 6 - 8 -10 -12 -16 - 20 - 25	8

	COD.	DESCRIPTION	DIAMETERS	N°OF COLLETS
IN PLASTIC TRAY	7593	ER 16 RF Complete	from Ø 3 to Ø10	8
	7594	ER 20 RF Complete	from Ø 3 to Ø13	11
	7595	ER 25 RF Complete	from Ø 3 to Ø16	14
	7596	ER 32 RF Complete	from Ø 3 to Ø20	18
	7597	ER 40 RF Complete	from Ø 4 to Ø26	23
IN WOODEN CASE	7606	ER 16 RF Complete	from Ø 3 to Ø10	8
	7607	ER 20 RF Complete	from Ø 3 to Ø13	11
	7608	ER 25 RF Complete	from Ø 3 to Ø16	14
	7609	ER 32 RF Complete	from Ø 3 to Ø20	18
	7610	ER 40 RF Complete	from Ø 4 to Ø26	23