









Insert

Application	Picture	Designation	Coated						Dimensions (mm)					Configuration	Page
			NC3215	NC3225	NC5330	NC6315	PC5300	PC9030	b	r	l	d	α°		
Grooving		KG MN	200-02-L	●	●		●	●	2.0	0.2	20	1.7	-		C14~21 C23
			300-02-L	●	●		●	●	3.0	0.2	20	2.3	-		
			400-02-L	●	●		●	●	4.0	0.2	20	3.3	-		
			500-03-L	●	●		●		5.0	0.3	25	4.1	-		
			600-03-L	●	●		●		6.0	0.3	25	5.1	-		
Grooving · Parting off		KG MN	150-015-R	●	●		●		1.5	0.15	16	1.2	-		C14~21 C23
			200-02-R	●	●		●	●	2.0	0.2	20	1.7	-		
			300-02-R	●	●		●	●	3.0	0.2	20	2.3	-		
			400-03-R	●	●		●	●	4.0	0.3	20	3.3	-		
			500-03-R		●		●		5.0	0.3	25	4.1	-		
			600-03-R		●		●		6.0	0.3	25	5.1	-		
			800-04-R		●		●		8.0	0.4	30	6.1	-		
Grooving · Turning		KG MN	150-015-T	●	●	●	●		1.5	0.15	16	1.2	-		C14~21 C23
			200-02-T	●	●	●	●	●	2.0	0.2	20	1.7	-		
			250-02-T	●	●		●		2.5	0.2	20	2.0	-		
			300-02-T	●	●	●	●	●	3.0	0.2	20	2.3	-		
			04-T	●	●	●	●	●	3.0	0.4	20	2.3	-		
			400-04-T	●	●	●	●	●	4.0	0.4	20	3.3	-		
			08-T	●	●	●	●	●	4.0	0.8	20	3.3	-		
			500-04-T	●	●	●	●	●	5.0	0.4	25	4.1	-		
			08-T	●	●	●	●	●	5.0	0.8	25	4.1	-		
			600-04-T	●	●	●	●	●	6.0	0.4	25	5.1	-		
			08-T	●	●	●	●	●	6.0	0.8	25	5.1	-		
			800-08-T	●		●	●		8.0	0.8	30	6.1	-		
Relief Profiling		KR MN	200-C	●	●	●	●		2.0	1.0	20	1.7	-		C14~22
			300-C	●	●		●		3.0	1.5	20	2.2	-		
			400-C	●	●	●	●		4.0	2.0	20	3.2	-		
			500-C	●	●	●	●		5.0	2.5	25	4.0	-		
			600-C	●	●	●	●		6.0	3.0	25	5.0	-		
			800-C	●	●	●	●		8.0	4.0	30	6.0	-		
Profiling		KR MI	200-C						2.0	1.0	20	1.7	-		C23
			300-C						3.0	1.5	20	2.2	-		
			400-C						4.0	2.0	20	3.2	-		
Grooving · Internal		KG MI	200-02-T				●		2.0	0.2	20	1.7	-		C23
			300-04-T				●		3.0	0.4	20	2.3	-		
			400-04-T				●		4.0	0.4	20	3.3	-		
Parting off (Right handed)		KG MR	200-6D-LP		●		●		2.0	0.2	20	1.7	6		C14 C16
			8D-LP						2.0	0.2	20	1.7	8		
			15D-LP		●		●		2.0	0.2	20	1.7	15		
			300-6D-LP		●		●		3.0	0.2	20	2.3	6		
			15D-LP		●		●		3.0	0.2	20	2.3	15		
			400-4D-LP		●		●		4.0	0.3	20	3.3	4		
			15D-LP		●		●		4.0	0.3	20	3.3	15		
Parting off (Right handed)		KG MR	500-4D-LP						5.0	0.3	25	4.1	4		C14 C16
			200-6D-RP		●		●		2.0	0.2	20	1.7	6		
			8D-RP						2.0	0.2	20	1.7	8		
			15D-RP		●		●		2.0	0.2	20	1.7	15		
			300-6D-RP		●		●		3.0	0.2	20	2.3	6		
			15D-RP		●		●		3.0	0.2	20	2.3	15		
			400-4D-RP		●		●		4.0	0.3	20	3.3	4		
			15D-RP		●		●		4.0	0.3	20	3.3	15		
			500-4D-RP						5.0	0.3	25	4.1	4		

• You can grind the chip breaker, 'B' as any shape you want. If you want any special shape of chip breaker, please contact your distributor.

● : Stock item